

Edraw Viewer Component for Word V7

User's Guide

©2004 - 2010 EdrawSoft.
All right reserved.
Edraw and Edraw logo
are registered trademarks
of EdrawSoft.

Contents

Edraw Viewer Component for Word.....	3
Methods	5
Event.....	31
Property	35
Constants.....	36
System Requirements	40
Redistribute Files.....	41
Visual Basic Issue	42
Visual C++ Issues	43
Web Application Issue	44
Convert to Full Version	46

Edraw Viewer Component for Word

Edraw Viewer Component for Word contains a standard ActiveX control that acts as an ActiveX document container for hosting MS Word documents in a custom form or Web page. The control is lightweight and flexible, and gives developers new possibilities for using Office in a custom solution.

The control is designed to handle specific issues that make using ActiveX documents from a non-top-level host window difficult, and serves as a starting place for constructing your own embedded object file viewer or editor as an ActiveX control.

It is a great solution for companies wishing to display read-only Word document data to their employees while restricting modifications to the underlying data. You can also display password protected Word documents without supplying passwords to your users - keep your confidential data safe and secure! With the Word component it is easy to upload or download file between server and client via HTTP/FTP.

How to add “Edraw Viewer Component for Word” to your Visual Basic 6.0 project

1. From the Project Menu select Components...
2. Select control “EDWord ActiveX Control Module” in the controls table
3. Click the OK Button
4. The control will now appear in your toolbox
5. Drag and drop the control on your form

How to add “Edraw Viewer Component for Word” to your .NET project

1. Open .NET
2. Right-click on the toolbox and select "Choose Items..."
3. Select the COM Components Tab
4. Check “EDWord Control” and click OK Button
5. The control should appear in the toolbox as "Edraw Viewer Component For Word"
6. Double-click on the control to add to your form
7. Resize and move the control on the form as desired
8. Add a button to the form
9. Double-click on the button to access code editor and enter the following code within the Click event: Note: Modify code to point to an existing document file on your web server
10. EDWord1.Open "
<http://www.edrawsoft.com/demo/samples/sample.doc>"
11. Run the application and click on the button

For ASP.NET or PHP project, you needn't add the component to the toolbar.
View the “read me.txt” file in the “install folder\samples\ASP.NET\” folder

Methods

boolean IsWordInstalled();

Returns whether the client installs the MS Word program.

IDispatch ActiveDocument();*

Returns the Automation interface of the document object.

The method allows you to obtain a reference to the IDispatch interface of the embedded object. From this interface you can automate the object to perform tasks, edit parts of the document, or gather information about what a user has added or removed.

For example, if you have a Word document open, you can use code that resembles the following to add a line of text:

```
<script language="vbscript">
Sub OfficeAutomationDemo()
OfficeViewer1.NewDoc
Set objWord = edword.ActiveDocument
edword.Content.Text = "This was added by Automation"
End Sub
</script>
```

or

```
<script language="javascript">
function WordAutomation()//Use the follow Javascript to insert a file in the
header of MS Word.
{
document.OA1.CreateNew("Word.Document");
var objWord = document.OA1.ActiveDocument;
objWord.Sections(1).Headers(1).Range.InsertFile("c:\\test.docx");
}
</script>
```

*IDispatch * **GetApplication**();*

Returns the Automation interface of the application.

*boolean **NewDoc**([in, optional] *VARIANT TemplatePath*, [in, optional] *VARIANT NewTemplate*);*

Creates a new, empty document.

TemplatePath: The name of the template to be used for the new document. If this argument is omitted, the Normal template is used.

NewTemplate: True to open the document as a template. The default value is False.

Example

The following vb script shows how to open word template.

```
Sub NewDoc_Example()  
edword.NewDoc "c:\test.dot", true  
End Sub
```

*boolean **Open**(*BSTR FileName*);*

Opens the specified document.

FileName: The name of the document (needs the full paths or url).

Example

The following vb script shows how to open word file.

```
Sub LoadFile_Example()  
edword.Open "c:\test.docx"  
End Sub
```

```
Sub LoadURL_Example()  
edword.Open "http://www.ocxt.com/demo/samples/sample.doc"  
End Sub
```

*boolean **Save**();*

Saves the specified document. If the document hasn't been saved before, the Save As dialog box prompts the user for a file name.

boolean SaveAs([in] BSTR FilePath, [in, optional] VARIANT FileFormat);

Saves the document to specified location with the specified format.

FilePath: The name for the document. If a document with the specified file name already exists, the document is overwritten without the user being prompted first.

FileFormat: The format in which the document is saved. Can be any WdSaveFormat constant.

```
enum WdSaveFormat
{
    wdFormatDocument = 0,
    wdFormatTemplate = 1,
    wdFormatText = 2,
    wdFormatTextLineBreaks = 3,
    wdFormatDOSText = 4,
    wdFormatDOSTextLineBreaks = 5,
    wdFormatRTF = 6,
    wdFormatUnicodeText = 7,
    wdFormatEncodedText = 7,
    wdFormatHTML = 8,
    wdFormatWebArchive = 9,
    wdFormatFilteredHTML = 10,
    wdFormatXML = 11
}WdSaveFormat;
```

Example

The following vb script shows how to save as a word document.

```
Sub SaveAs_Example()
edword.SaveAs "c:\test.docx"
End Sub
```

boolean CloseDoc([in, optional] VARIANT SaveChanges);

Closes the specified document or documents.

SaveChanges: Specifies the save action for the document. Can be one of the following WdSaveOptions constants: wdDoNotSaveChanges, wdPromptToSaveChanges, or wdSaveChanges.

```
enum WdSaveOptions
{
    wdDoNotSaveChanges = 0,
    wdSaveChanges = -1,
    wdPromptToSaveChanges = -2
};
```

boolean IsDirty();

Returns True/False if file has been altered or needs save.

boolean IsOpened();

Returns True/Fase if file has been opened.

boolean OpenFileDialog([in, optional] VARIANT Filter);

Calls the standard file dialog to open the office document.

Filter: The file filter string.

Example

The following vb script shows how to open only the docx file dialog.

```
Sub OpenFileDialog_Example()  
edword.OpenFileDialog "All Word Files  
(*.*docx;*.docm;*.dotx;*.dotm;*.doc;*.dot;*.rtf;*.htm;*.mht;*.mhtml;*.xml;*.odt)|*.docx;*.docm;*.dotx;*.dotm;*.doc;*.dot;*.rtf;*.htm;*.mht;*.mhtml;*.xml;*.odt;*.txt;*.wps;*.wtf|Word Document(*.docx)|*.docx|Word 97-2003 Files(*.doc)|*.doc|All Files|*.*||"  
End Sub
```

boolean SaveFileDialog([in, optional] VARIANT Filter);

Calls the standard file dialog to save the office document.

Filter: The file filter string.

boolean PageSetupDialog();

Calls the page setup dialog.

boolean DocPropertiesDialog();

Call the document properties dialog.

boolean PrintDialog();

Calls the print dialog.

boolean PrintOut(WdPrintOutRange PrintRange, [in, optional] VARIANT FromPage, [in, optional] VARIANT ToPage, [in, optional] VARIANT Pages, [in, optional] VARIANT Copies);

Prints all or part of the specified document with settings.

PrintRange: Optional Object. The page range. Can be any WdPrintOutRange constant.

FromPage: Optional Object. The starting page number when Range is set to wdPrintFromTo.

ToPage: Optional Object. The ending page number when Range is set to wdPrintFromTo.

Pages: Optional Object. The page numbers and page ranges to be printed, separated by commas. For example, "2, 6-10" prints page 2 and pages 6 through 10.

Copies: Optional Object. The number of copies to be printed.

```
enum WdPrintOutRange
{
    wdPrintAllDocument = 0,
    wdPrintSelection = 1,
    wdPrintCurrentPage = 2,
    wdPrintFromTo = 3,
    wdPrintRangeOfPages = 4
};
```

Example

The following vb script shows how to print the 3-6 page in a document.

```
Sub PrintOut_Example()
edword.PrintOut 3, 3, 6
End Sub
```

boolean PrintPreview();

Starts a print preview.

boolean PrintPreviewExit();

Exits a current print preview.

boolean SetValue([in] BSTR Name, [in] BSTR Value);

Sets the password, writepassword, domain and protectmodereminder for the document.

Name: The name string.

Value: The value string.

Example

The following vb script shows how to open a password-protected document. if the 1.docx file has the password 1234, the writepassword 5678, you can use the follow sample.

```
Sub SetValue_Example()  
edword.SetValue "Password", "1234"  
edword.SetValue "WritePassword", "5678"  
'edword.SetValue "Domain", "www.edrawsoft.com"  
'edword.SetValue "ProtectModeReminder", "The ActiveX Controls is not available for Internet  
sites under the enhanced security configuration."  
edword.Open "c:\1.docx"  
End Sub
```

boolean *ProtectDoc*(*WdProtectType ProtectType*, [*in, optional*] *VARIANT Password*);

Helps to protect the specified document from changes. When a document is protected, users can make only limited changes, such as adding annotations, making revisions, or completing a form.

ProtectType: The protection type for the specified document. WdProtectionType.

Password: Optional Object. The password required to remove protection from the specified document.

```
enum WdProtectType  
{  
    wdAllowOnlyRevisions = 0,  
    wdAllowOnlyComments = 1,  
    wdAllowOnlyFormFields = 2,  
    wdAllowOnlyReading = 3,  
    wdNoProtection = -1,  
}WdProtectType;
```

Example

The following vb script shows how to protect a document for only revisions.

```
Sub ProtectDoc_Example()  
edword.ProtectDoc 0  
End Sub
```

boolean *UnProtectDoc*([*in, optional*] *VARIANT Password*);

Removes protection from the specified document. If the document isn't protected, this method generates an error.

Password: Optional Object. The password required to remove protection from the specified document.

Example

The following vb script shows how to unprotect a document with password 832-f2322.

```
Sub Unprotect_Example()  
edword.UnProtectDoc "832-f2322"  
End Sub
```

BSTR *GetDocumentName()*;

Returns the name of the specified object.

BSTR *GetDocumentFullName()*;

Specifies the name of a document, template, or cascading style sheet, including the drive or Web path.

boolean *IsReadOnly()*;

Determines if changes to the document cannot be saved to the original document.

boolean *DisableSaveHotKey(boolean Disable)*;

Disables the Save keycodes.

Disalbe: Disables the CTRL+S, SHIFT+F12, Alt+SHIFT+F2, F12

boolean *DisablePrintHotKey(boolean Disable)*;

Disables the Print keycodes.

Disalbe: Disables the CTRL+P, CTRL+SHIFT+F12, CTRL+F2, ALT+CTRL+I

boolean DisableCopyHotKey(boolean Disable);

Disables the Copy keycodes.

Disalbe: Disables the CTRL+C, CTRL+V, CTRL+X, SHIFT+DEL, SHIFT+INSERT, ALT+CTRL+V, CTRL+SHIFT+C, CTRL+INSERT

boolean DisplayHorizontalRuler([in] boolean Show);

Shows/Hides the horizontal ruler in the office program.

boolean DisplayVerticalRuler([in] boolean Show);

Shows/Hides the vertical ruler in the office program.

boolean DisplayGridline([in] boolean Show);

Shows/Hides the grid lines in the office program.

boolean SwitchViewType([in] WdViewType ViewType);

Switches to the different view for office program.

ViewType: The view type for the specified document. WdViewType.

```
enum WdViewType
{
    wdMasterView = 5,
    wdNormalView = 1 ,
    wdOutlineView = 2,
    wdPrintPreview = 4 ,
    wdPrintView = 3,
    wdReadingView = 7,
    wdWebView = 6,
}WdViewType;
```

Example

The following vb script shows how to switch to webview after document opened.

```
Sub DocumentOpenedEvent ()
    Edward.SwitchViewType 6
```

```
End Sub
```

```
<SCRIPT FOR=OA1 EVENT= DocumentOpened ()>  
    DocumentOpenedEvent()  
</SCRIPT>
```

boolean ViewZoomTo([in] WdPageFit FitType, [in, optional] VARIANT ZoomFactor);

Zooms to the special zoom factor.

FitType: The zoom mode for the specified document. WdPageFit.

ZoomFactor: The zoom factor.

```
enum WdPageFit  
{  
    wdPageFitTextNone = 0 ,  
    wdPageFitFullPage = 1,  
    wdPageFitBestFit = 2,  
    wdPageFitTextFit = 3 ,  
}WdPageFit;
```

Example

The following vb script shows how to zoom the document to 200%.

```
Sub DocumentOpenedEvent ()  
Edword.ViewZoomTo -1, 200  
' fit best fit  
'Edword.ViewZoomTo 2  
End Sub  
  
<SCRIPT FOR=OA1 EVENT= DocumentOpened ()>  
    DocumentOpenedEvent()  
</SCRIPT>
```

boolean ShowRevisions([in] boolean Show);

Shows/Hides the revisions for the office program.

boolean AcceptAllRevisions([in] boolean Receipt);

Accepts or rejects all the tracked changes in a document or range.

long GetBookmarkCount();

Returns the number of bookmarks.

BSTR ReadBookmarkInfo([in] long Pos, [in] boolean NameOrValue);

Returns the name or value of the special bookmark.

Pos: The index of bookmarks in the document. From 1 to ...

NameOrValue: True returns the bookmark name, False returns the bookmark value.

Example

The following java script shows how to read the bookmark information.

```
function Readbookmark_Example ()
{
  Var count = edword.GetBookmarkCount();
  For(int i=1; i<=count; i++)
  {
    Var name = edword.GetBookmarkInfo(i, true);
    Var value = edword.GetBookmarkInfo(i, false);
  }
}
```

boolean WriteBookmarkInfo([in] BSTR Name, [in] BSTR Value);

Writes the value for the special bookmark.

Name: The bookmark name.

Value: The bookmark value.

boolean InsertFile([in] BSTR FilePath, [in, optional] VARIANT InDocPos);

Inserts a file to opened Word file.

FilePath: The file path need to be inserted.

InDocPos: The insert position. WdInPocPos.

```
enum WdInDocPos
{
    wdInDocumentPosCursor = 1,
    wdInDocumentPosStart = 2,
    wdInDocumentPosEnd = 3 ,
}WdInDocPos;
```

boolean InsertText([in] BSTR Text, [in, optional] VARIANT InDocPos);

Inserts text content to opened Word file.

Text: The text string need to be inserted.

InDocPos: The insert position. WdInPocPos.

```
enum WdInDocPos
{
    wdInDocumentPosCursor = 1,
    wdInDocumentPosStart = 2,
    wdInDocumentPosEnd = 3 ,
}WdInDocPos;
```

boolean InsertPicture([in] BSTR FilePath, [in] boolean InlineObject, [in, optional] VARIANT InDocPos);

Inserts a picture to opened Word file.

FilePath: The image path need to be inserted.

InDocPos: The insert position. WdInPocPos.

```
enum WdInDocPos
{
    wdInDocumentPosCursor = 1,
    wdInDocumentPosStart = 2,
    wdInDocumentPosEnd = 3 ,
}WdInDocPos;
```

boolean InsertBreak([in] WdBreakType BreakType);

Inserts a break to opened Word file.

BreakType: The break type. WdBreakType.

```
typedef enum WdBreakType
{
    wdPageBreak = 7,
    wdColumnBreak = 8,
    wdSectionBreakNextPage = 2,
    wdSectionBreakContinuous = 3,
    wdSectionBreakEvenPage = 4,
    wdSectionBreakOddPage = 5,
    wdLineBreak = 6,
    wdLineBreakClearLeft = 9,
    wdLineBreakClearRight = 10,
```

```
        wdTextWrappingBreak = 11,  
    }WdBreakType;
```

Example

The following java script shows how to insert a line break.

```
function InsertBreak_Example ()  
{  
    Edword.InsertBreak( 6 );  
}
```

***boolean** **GotoItem**(**[in]** **WdGoToItem** **What**, **[in]** **WdGoToDirection** **Which**, **[in, optional]** **VARIANT** **Count**, **[in, optional]** **VARIANT** **Name**);*

Goes to the specified item in the Word document.

What: Optional Object. The kind of item to which the range or selection is moved. Can be one of the WdGoToItem constants.

Which: Optional Object. The item to which the range or selection is moved. Can be one of the WdGoToDirection constants.

Count: Optional Object. The number of the item in the document. The default value is 1. Only positive values are valid. To specify an item that precedes the range or selection, use wdGoToPrevious as the Which argument and specify a Count value.

Name: Optional Object. If the What argument is wdGoToBookmark, wdGoToComment, wdGoToField, or wdGoToObject, this argument specifies a name.

```
enum WdGoToItem  
{  
    wdGoToStart = 101,  
    wdGoToEnd = 102,  
    wdGoToBookmark = -1 ,  
    wdGoToComment = 6 ,  
    wdGoToEndnote = 5 ,  
    wdGoToEquation = 10 ,  
    wdGoToField = 7 ,  
    wdGoToFootnote = 4 ,  
    wdGoToGrammaticalError= 14 ,  
    wdGoToGraphic = 8 ,  
    wdGoToHeading= 11 ,  
    wdGoToLine = 3 ,  
    wdGoToObject = 9 ,  
    wdGoToPage = 1 ,  
    wdGoToPercent = 12 ,  
    wdGoToProofreadingError = 15 ,  
    wdGoToSection = 0 ,  
    wdGoToSpellingError = 13 ,  
    wdGoToTable = 2 ,  
}WdGoToItem;
```

```
enum WdGoToDirection
{
    wdGoToAbsolute = 1,
    wdGoToFirst = 1,
    wdGoToLast = -1,
    wdGoToNext = 2,
    wdGoToPrevious = 3,
    wdGoToRelative = 2,
}WdGoToDirection;
```

Example

The following java script shows how to go to the file end.

```
function GoToItem_Example ()
{
    Edward.GoToItem( 102, 1 );
}
```

boolean ReplaceText([in] BSTR Text, [in] BSTR ReplaceText, [in] boolean MatchWholeWord, [in] boolean MatchCase);

Replaces all the specified string value with another string value.

Text: Optional Object. The text to be searched for.

ReplaceText: The replacement text.

MatchCase: Optional Object. True to specify that the find text be case-sensitive. Corresponds to the Match case check box in the Find and Replace dialog box (Edit menu).

MatchWholeWord: Optional Object. True to have the find operation locate only entire words, not text that's part of a larger word. Corresponds to the Find whole words only check box in the Find and Replace dialog box.

boolean MergeAndCompare([in] BSTR TargetFilePath);

Compares and merges documents then displays it in the current windows.

TargetFilepath: Required String.

boolean DisableDragAndDrop(boolean Disable);

Disables drag and drop.

long GetRevisionCount();

Returns the number of Revisions.

BSTR ReadRevisionInfo([in] long Pos, [in] WdRevisionType RevType);

Returns the name or value of the special bookmark.

Pos: The index of bookmarks in the document. From 1 to ...

RevType: The revision type. WdRevision.

```
enum WdRevisionType
{
    wdRevisionAuthor = 0,
    wdRevisionDate = 1,
    wdRevisionType = 2,
    wdRevisionText = 3,
}WdRevisionType;
```

Example

The following java script shows how to read the bookmark information.

```
function ReadRevision_Example ()
{
    Var count = edword.GetRevisionCount();
    For(int i=1; i<=count; i++)
    {
        Var author = edword.ReadRevisionInfo(i, 0);
        Var text = edword. ReadRevisionInfo (i, 3);
    }
}
```

boolean AcceptRevision([in] long Pos, [in] boolean Accept);

Accepts or rejects the specified tracked change.

Pos: The index of bookmarks in the document. From 1 to ...

Accept: Accepts or rejects the revision.

boolean DisableViewRightClickMenu(boolean Disable);

Disables the right click menu in the MS Word.

boolean CopyToClipboard();

Copies the whole content to the clipboard.

boolean CopyToClipboardAsPicture();

Copies the whole content to the clipboard as picture.

boolean PasteFromClipboard([in, optional] VARIANT InDocPos);

Pastes to the opened Word file from the clipboard data.

InDocPos: The position. WdInDocPos.

```
enum WdInDocPos
{
    wdInDocumentPosCursor = 1,
    wdInDocumentPosStart = 2,
    wdInDocumentPosEnd = 3 ,
}WdInDocPos;
```

boolean PasteSpecialFromClipboard([in] WdPasteDataType IFormatType, [in] boolean vFloatOverText, [in, optional] VARIANT InDocPos);

Pastes to the opened Word file from the clipboard data with special format.

IFormatType: Paste format type. WdPasteDataType.

vFloatOverText: True = float the object over text.

InDocPos: The position. WdInDocPos.

```
enum WdPasteDataType
{
    wdPasteBitmap = 4,
    wdPasteDeviceIndependentBitmap = 5,
    wdPasteEnhancedMetafile = 9,
    wdPasteHTML = 10,
    wdPasteHyperlink = 7,
    wdPasteMetafilePicture = 3,
    wdPasteOLEObject = 0,
    wdPasteRTF = 1,
    wdPasteShape = 8,
    wdPasteText = 2,
}WdPasteDataType;
```

boolean DisableFileCommand([in] WdUIType UIType, [in] boolean Disable);

UIType: The enum type need to disable in the UI. WdUIType.

Disable: True to disable the command button or menu item.

```
enum WdUIType
{
    wdUIDisalbeOfficeButton = 0x00000001,
    wdUIDisalbeNew           = 0x00000002,
    wdUIDisalbeOpen          = 0x00000004,
    wdUIDisalbeUpgradeDocument = 0x00000008,
    wdUIDisalbeSave          = 0x00000010,
    wdUIDisalbeSaveAs        = 0x00000020,
    wdUIDisalbeSendAsAttachment = 0x00000040,
    wdUIDisalbeClose         = 0x00000100,
    wdUIDisalbePrint         = 0x00000200,
    wdUIDisalbePrintQuick    = 0x00000400,
    wdUIDisalbePrintPreview  = 0x00000800,
    wdUIDisalbeSaveAsMenu    = 0x00001000,
    wdUIDisalbePrepareMenu   = 0x00002000,
    wdUIDisalbePermissionRestrictMenu = 0x00004000,
    wdUIDisalbeSendMenu      = 0x00008000,
    wdUIDisalbePublishMenu   = 0x00010000,
    wdUIDisalbeServerTasksMenu = 0x00020000,
    wdUIDisalbeCopyButton    = 0x00040000,
    wdUIDisalbeCutButton     = 0x00080000,
    wdUIHideMenuHome        = 0x01000000,
    wdUIHideMenuInsert      = 0x02000000,
    wdUIHideMenuPageLayout  = 0x04000000,
    wdUIHideMenuReferences  = 0x08000000,
    wdUIHideMenuMailings    = 0x10000000,
    wdUIHideMenuReview      = 0x20000000,
    wdUIHideMenuView        = 0x40000000,
    wdUIHideMenuDeveloper   = 0x80000000,
    wdUIHideMenuAddIns      = 0x00100000,
    wdUIHideMenuFormat      = 0x00200000,
    wdUIHideMenuEdit        = 0x00400000,
    wdUIHideMenuTool        = 0x00800000,
}WdUIType;
```

Note: The component disabled the Office menu, New button and Open button in default.

```
DWORD dwDisableCommand = wdUIDisalbeOfficeButton |
wdUIDisalbeNew| wdUIDisalbeOpen;
```

The function need be set in the BeforeDocumentOpened event.

If you want to enable the three button, follow the samples.

Example

The following vb script shows how to enable the office main menu, new button and open button.

```
Sub DocumentOpenedEvent ()  
Edword.DisableFileCommand 1 , false           'wdUIDisalbeOfficeButton  
Edword.DisableFileCommand 2 , false           'wdUIDisalbeNew  
Edword.DisableFileCommand 4 , false           'wdUIDisalbeOpen  
End Sub  
  
<SCRIPT FOR=OA1 EVENT= DocumentOpened ()>  
    DocumentOpenedEvent()  
</SCRIPT>
```

The following vb script shows how to diable the saveas and save button.

```
Sub DocumentOpenedEvent ()  
Edword.DisableFileCommand 16 , true           'wdUIDisalbeSave  
Edword.DisableFileCommand 32 , true           'wdUIDisalbeSaveAs  
End Sub  
  
<SCRIPT FOR=OA1 EVENT= DocumentOpened ()>  
    DocumentOpenedEvent()  
</SCRIPT>
```

BSTR GetOfficeVersion();

Returns the version number of the office program.

long GetCurrentPageIndex();

Returns the current page index in the word.

long GetPageCount();

Returns the total page counts in the word.

boolean UpdateOffice2003ToolbarButton([in] long OfficeID, [in] boolean Visible, [in] boolean Enabled);

Disables or hides the office 2000, 2003 toolbar button.

OfficeID: The office MSO id for every button.

Visible: True to set the command button visible.

Enabled: True to enable the command button.

The function works only in the Office 2000/2003 version.

The following vb script shows how to hide the saveas and save button.

```
Sub DocumentOpenedEvent ()
Edword.UpdateOffice2003ToolbarButton 3 , false, false           'save button
Edword.UpdateOffice2003ToolbarButton 748 , false, false         'saveas button
End Sub

<SCRIPT FOR=OA1 EVENT= DocumentOpened ()>
    DocumentOpenedEvent()
</SCRIPT>
```

boolean InvisibleOffice2003Toolbar([in] BSTR ToolbarName);

Disables or hides the office 2000, 2003 toolbar.

ToolbarName: The office 2000, 2003 commandbar name.

The following vb script shows how to hide the standard toolbar, web toolbar and formatting toolbar.

```
Sub DocumentOpenedEvent ()
Edword.InvisibleOffice2003Toolbar "Standard"
Edword.InvisibleOffice2003Toolbar "Web"
Edword.InvisibleOffice2003Toolbar "Formatting"
End Sub

<SCRIPT FOR=OA1 EVENT= DocumentOpened ()>
    DocumentOpenedEvent()
</SCRIPT>
```

boolean HttpInit();

Initializes the HTTP connection.

boolean HttpAddPostString(BSTR Name, BSTR Value);

Adds the post parameter.

Name: The parameter name.

Value: The parameter value.

boolean HttpAddPostFile(BSTR LocalFilePath, [in, optional] VARIANT NewFileName);

Adds the post file.

LocalFilePath: The full file path needs to upload to the server. If the parameter is NULL, the function will add the file which is opening in the component.

NewFileName: The new file name for the upload file.

boolean HttpAddPostOpenedFile([in, optional] VARIANT NewFileName);

Adds the opened office file to post queue.

NewFileName: The new file name for the upload file.

boolean HttpPost(BSTR WebUrl, [in, optional] VARIANT WebUsername, [in, optional] VARIANT WebPassword);

Sends the specified request to the HTTP server.

WebUrl: A string containing the web url from which uploads data via HTTP.

WebUsername: A string containing the user name.

WebPassword: A string containing the access password.

The follow code is demo how to upload the opened file to server with the HTTP mode. It can also post multiple files in a post request.

```
<script language="vbscript">
Sub UploadFile()
edword.HttpInit
edword.HttpAddpostString "author", "anyname"
edword.HttpAddpostString "Data", "2010-5-15"
edword.HttpAddPostOpenedFile
edword.HttpPost "http://localhost:1320/Samples/UploadAction.aspx"
End Sub
</script>
```

Note: If you try to save the opened file to remote server with the "HTTP" methods, you need write a receipt page in your web server. Because the component uploads the file by HTTP mode. The follow is some sample code.

```
ASP.NET:
//Default.aspx
<script language="vbscript">
Sub SavetoServer()
edword.HttpInit
edword.HttpAddpostString "author", "anyname"
edword.HttpAddpostString "Data", "2010-5-15"
edword.HttpAddPostOpenedFile
```

```
edword.HttpPost "http://localhost:1320/Samples/UploadAction.aspx"
'edword.Save "http://localhost:1320/UploadAction.aspx?author=name&Data=2"
End Sub
</script>
```

```
//UploadAction.aspx.cs file
```

```
using System;
using System.Collections;
using System.ComponentModel;
using System.Data;
using System.Drawing;
using System.IO;
using System.Web;
using System.Web.SessionState;
using System.Web.UI;
using System.Web.UI.HtmlControls;
using System.Xml;
using System.Drawing.Imaging;
using System.Text.RegularExpressions;
```

```
public partial class UploadAction : System.Web.UI.Page
{
    protected void Page_Load(object sender, EventArgs e)
    {
        if (Request.QueryString["author"] == "name" && Request.QueryString["Data"] == "2")
        {
            Response.Write("0\n");
            Response.Write("We have receipted the right param from Edraw Diagram ActiveX
Control.");
        }
        if (Request.Files.Count == 0)
        {
            Response.Write("0\n");
            Response.Write("There isn't file to upload.");
            Response.End();
        }
        if (Request.Files[0].ContentLength == 0)
        {
            Response.Write("0\n");
            Response.Write("Failed to receipt the data.\n\n");
            Response.End();
        }
        string fullFileName = Server.MapPath(Request.Files[0].FileName);
        Request.Files[0].SaveAs(fullFileName);
        Response.Write("Upload Successfully.");
        Response.End();
    }
}
```

```
PHP:
```

```
<?php
header("http/1.1 200 OK");
$user = iconv("UTF-8", "UNICODE", $_POST['user']);
$password = iconv("UTF-8", "UNICODE", $_POST['password']);
$sql = sprintf("username=%s password=%s", $user,$password);
echo $sql;
$sql = sprintf("file=%s size=%s error=%s tmp=%s",
$_FILES['trackdata']['name'],$_FILES['trackdata']['size'],$_FILES['trackdata']['error'],$_FILES
['trackdata']['tmp_name']);
```

```

echo $sql;
$handle = fopen($_FILES['trackdata']['name'], "w+");
if($handle == FALSE)
{
    exit("Create file error!");
}
$handle2 = fopen($_FILES['trackdata']['tmp_name'], "r");
$data = fread($handle2, $_FILES['trackdata']['size']);
echo $data;
fwrite($handle, $data);
fclose($handle2);
fclose($handle);
exit(0);
?>

```

ASP: (review the full code in the install folder\samples\asp\)

```

<%@Language=VBScript %>
<!-- #include file=".include/upload.inc" -->
<!-- #include file=".include/conn.asp" -->
<%
Set Uploader = New UpFile_Class
Uploader.NoAllowExt="cs;vb;js;exe"
Uploader.GetData (Request.TotalBytes)
Request.TotalBytes
if Uploader.isErr then
    select case Uploader.isErr
        case 1
            Response.Write "Fail to receipt the data."
        case 2
            Response.Write "The file is too big to upload"
        End select
    'Response.End
End if
Dim id
If "" <> Request.QueryString("id") then
    id = Request.QueryString("id")
End if
if id <> 0 then
    Sql="SELECT * from doc where doc.id = "&id
else
    Sql="SELECT * from doc"
End if
rs.Open Sql,conn,1, 3
for each formName in Uploader.file
    set file=Uploader.file(formName)
    If id <> 0 then
        If("" = Request.QueryString("isAip")) Then
            rs("DocContent") = Uploader.FileData(formname)
            rs("DocID") = Uploader.Form("DocID")
            rs("DocTitle") = Uploader.Form("DocTitle")
            rs("DocType") = Uploader.Form("DocType")
        Else rs("AipContent") = Uploader.FileData(formname)
            rs("state") = 2
        End if
    Else
        rs.AddNew
        rs("DocID") = Uploader.Form("DocID")
        rs("DocTitle") = Uploader.Form("DocTitle")
        rs("DocContent") = Uploader.FileData(formname)
    End if
End for

```

```

        rs("Docdate") = Now()
        rs("DocType") = Uploader.Form("DocType")
        rs("state") = 1
    End If
set file=nothing
rs.Update
exit for
next
rs.Close
Set rs=Nothing
conn.close
set conn = Nothing
Set Uploader = Nothing
%>

JSP:
jsp:
<%@ page contentType="text/html; charset=UTF-8" %>
<%@ page language="java" import="com.jspsmart.upload.File>
<jsp:useBean id="mySmartUpload" scope="page" class="com.jspsmart.upload.SmartUpload"
/>
<%
String sPath="C:\\\"
mySmartUpload.initialize(pageContext);
mySmartUpload.upload();
String TempName=mySmartUpload.getRequest().getParameter("TempName");
mySmartUpload.save(sPath);
File myFile =mySmartUpload.GetFiles().getFile(0);
%>

```

boolean HttpOpenFileFromStream(BSTR WebUrl, [in, optional] VARIANT WebUsername, [in, optional] VARIANT WebPassword);

Opens a file from a stream with the HTTP/HTTPS.

WebUrl: A string containing the web url from which downloads data via HTTP. The WebUrl must include the file extend name so that the component know the file type. For example: <http://www.edrawsoft.com/Getfile.aspx?ID=1002&FileName=guid.edxz>, or <http://www.edrawsoft.com/sample.docx>.

WebUsername: A string containing the user name.

WebPassword: A string containing the access password.

Example:

Either you want to open an appointed file or open a file from database, for client side, all what you need do is the same, like following:

```

<script language="vbscript">
Sub DownloadFile()
    edword.HttpInit();
    edword.HttpAddpostString("DocumentID", "Tester.doc");
    edword.HttpOpenFileFromStream(strDownloadPath,"", "");
End Sub
</script>

```

Before you call function `HttpOpenFileFromStream`, you should do two things, one is to initialize http for clearing all parameters and cookies in http, another thing is to appoint the file or database record. And then use `HttpOpenFileFromStream` to send the request to the destined webpage. Before `HttpOpenFileFromStream` send request, it will add a couple of parameters automatically.

`edword.AddPostArgument(L"EDA_GETSTREAMDATA", L"EDA_YES");` This couple of parameters tell the destined webpage edword will received file as stream.

At the web side, webpage will decide to read which file or database record according to the post parameters. And you should add boundary flag 'EDA_STREAMBOUNDARY' to file data, following is the asp.net demo.

```
if (Request.Params["EDA_GETSTREAMDATA"] == "EDA_YES")
{
    String fullFileName = Server.MapPath(Request.Params["DocumentID"]);
    Byte[] fs = File.ReadAllBytes(fullFileName);

    Response.Write("Get Stream Successfully!");
    Response.Write("EDA_STREAMBOUNDARY");
    Response.BinaryWrite(fs);
    Response.Write("EDA_STREAMBOUNDARY");
}
```

asp:

```
If I_bWrStreamBoundary
Then Response.Write "EDA_STREAMBOUNDARY"
While Not I_stream.EOS And Response.IsClientConnected
Response.BinaryWrite(I_stream.Read(I_nChunkSize))
Wend I_stream.Close
If I_bWrStreamBoundary
Then Response.Write EDA_STREAMBOUNDARY"
```

BSTR HttpDownloadFileToTempDir(BSTR WebUrl, [in, optional] VARIANT WebUsername, [in, optional] VARIANT WebPassword);

Downloads a file from a remote server then save it to OA temporary directory with HTTP.

WebUrl: A string containing the web url from which downloads data via HTTP. The WebUrl must include the file extend name so that the component know the file type. For example: `http://www.edrawsoft.com/Getfile.aspx?ID=1002&FileName=guid.edxz`, or `http://www.edrawsoft.com/sample.edxz`.

WebUsername: A string containing the user name.

WebPassword: A string containing the access password.

Return Value: Local temporary file path to save the download file.

The component provides the method to download file from a server then save to a local disk file. Support Http and HTTPS.

```
<script language="vbscript">
Sub DownloadFile()
    Dim sPath;
```

```
sPath = edword.HttpDownloadFileToTempDir "http://www.edrawsoft.com/demo/1.doc"  
edword.Open sPath  
End Sub  
</script>
```

Note: You should make sure you the file exists in the web site firstly. A simple method is to enter the WebUrl in the Internet Explore. If IE can download the file, the component can do it too.

FAQ: If you are using Windows 2003 as your server, you maybe need to add the mime types to Internet Information Server.

boolean FtpConnect(BSTR WebUrl, [in, optional] VARIANT WebUsername, [in, optional] VARIANT WebPassword);

Creates a FTP connect.

boolean FtpDownloadFile(BSTR RemoteFile, BSTR LocalFile);

Downloads a file from remote server then save it to local file with FTP.

RemoteFile: The remote file path which saves to FTP site.

LocalFile: The full file path which downloads to the local disk.

boolean FtpUploadFile(BSTR LocalFile, BSTR RemoteFile, boolean OverWrite);

Uploads a local disk file to remote server with FTP.

LocalFilePath: The full file path needs to upload to the server. If the parameter is NULL, the function will add the file which is opening in the component.

RemoteFile: The remote file path which saves to FTP site.

OverWrite: Overwrites the existed file if the same file exists at the FTP server.

boolean FtpDisconnect();

Closes the FTP Connect.

The follow code is demo how to download a file to local disk with the FTP mode.

```
<script language="vbscript">  
Sub UploadFileviaFTP()  
edword.FtpConnect "ftp.edrawsoft.com", "username", "password"  
edword.FtpDownloadFile "ftp.edrawsoft.com/archieve/001.doc", "c:\temp.doc"  
edword.FtpDisconnect
```

```
End Sub  
</script>
```

***long** **GetErrorCode()**;*

Returns the error code.

BSTR** **GetTempFilePath([in, optional] VARIANT RefFileName);

Gets a temporary file path.

RefFileName: The referent file name.

***boolean** **ClearTempFiles()**;*

Clears these temporary files created by the component. The function won't delete any other files out of temporary ED directory.

void** **ShowRibbonTitlebar([in] VARIANT_BOOL Show);

Shows/Hides the title bar in the office ribbon interface.

For Office 2007 and Office 2010, you can hide the Ribbon title bar with the method in the BeforeDocumentOpened event.

void** **ShowMenubar([in] VARIANT_BOOL Show);

Shows/Hides the menu bar in the office interface.

For Office 2000, Xp, 2003, you can hide the menu bar with the method in the BeforeDocumentOpened event. For office 2007 and higher version, you can use the DisableFileCommand method.

boolean SetComponentSize([in] long Width, [in] long Height);

Resizes the width and height of component.

void DisableStandardCommand([in] CommandType CmdType, [in] BOOL Disable);

Disables the standard file, save, print commands.

You can disable the standard commands in the office. Then write your own process in the event.

```
enum CommandType {
    cmdTypeSave = 0x00000001,
    cmdTypeClose = 0x00000002,
    cmdTypePrint = 0x00000004,
    cmdTypeRightClick = 0x00000008,
    cmdTypeDoubleClick = 0x00000010,
    cmdTypeIESecurityReminder = 0x00000020,
} CommandType;
```

The follow code is demo how to disable the print process.

```
function OA_DocumentBeforePrint()
{
    document.OA1.DisableStandardCommand(4, true); //cmdTypePrint = 0x00000004,
}
<script language="javascript" for="OA1" event="DocumentBeforePrint()">
    OA_DocumentBeforePrint();
</script>
```

Event

[id(1), helpstring("Occurs after the control has completed the initialization.")]

void NotifyCtrlReady();

Example

The following script to hide the toolbar and grid when the component was initialized.

```
function edword_NotifyCtrlReady()
{
    document.all.edword.LicenseName = "";
    document.all.edword.LicenseCode = "";
    document.all.edword.BorderStyle = 1;
    document.all.edword.Toolbars = false;
}
<SCRIPT LANGUAGE=javascript FOR=edword EVENT=NotifyCtrlReady>
<!--
    edword_NotifyCtrlReady();
//-->
</SCRIPT>
```

[id(2), helpstring("Called when the new document is created.")]

void NewDocument();

[id(3), helpstring("Called before document is opened or new document added.")]

void BeforeDocumentOpened();

Example

The following script to add office UI setting before a document opened.

```
function edword_BeforeDocumentOpened()
{
    Edword.DisableFileCommand 1 , false           'wdUIDisalbeOfficeButton
    Edword.DisableFileCommand 2 , false           'wdUIDisalbeNew
    Edword.DisableFileCommand 4 , false           'wdUIDisalbeOpen
    Edword.DisableFileCommand 16 , true            'wdUIDisalbeSave
```

```

        Edword.DisableFileCommand 32 , true                'wdUIDisalbeSaveAs
    }
    <SCRIPT LANGUAGE=javascript FOR=edword EVENT= BeforeDocumentOpened >
    <!--
        edword_ BeforeDocumentOpened ();
    //-->
</SCRIPT>

```

[id(4), helpstring("Called when document is opened or new document added.")]

void DocumentOpened();

Example

The following script to add office automation after a document was opened.

```

function edword_DocumentOpened()
{
    var objWord = document.OA1.ActiveDocument;
    document.OA1.GotoItem(101, 0); //move to start.
    document.OA1.InsertBreak(6); //insert a line break
    var range = objWord.Range(0,0);
    var WTable = objWord.Tables.Add(range, 3,3);
    WTable.Cell(1,1).Range.Font.Name = "Times New Roman";
    WTable.Cell(1,1).Range.Text = "Automation 1";
    WTable.Cell(1,2).Range.Font.Size = 18;
    WTable.Cell(1,2).Range.Bold = true;
    WTable.Cell(1,2).Range.Font.Italic = true;
    WTable.Cell(1,2).Range.Text = "Automation 2";
    WTable.Cell(2,1).Range.ParagraphFormat.Alignment = 1; // 0= Left, 1=Center,
2=Right
    WTable.Cell(2,1).Range.Font.Name = "Arial";
    WTable.Cell(2,1).Range.Font.Size = 12;
    WTable.Cell(2,1).Range.Bold = false;
    WTable.Cell(2,1).Range.ParagraphFormat.Alignment = 2;
    WTable.Cell(3,3).Range.Font.Name = "Times New Roman";
    WTable.Cell(3,3).Range.Font.Size = 14;
    WTable.Cell(3,3).Range.Bold = true;
    WTable.Cell(3,3).Range.Font.Underline = true;
    WTable.Cell(3,3).Range.ParagraphFormat.Alignment = 0;
    WTable.Cell(3,2).Range.Text = "Automation 3"; }
    <SCRIPT LANGUAGE=javascript FOR=edword EVENT= DocumentOpened >
    <!--
        edword_ DocumentOpened ();
    //-->
</SCRIPT>

```

[id(5), helpstring("Called before document is closed (may be canceled).")]

`void BeforeDocumentClosed();`

`[id(6), helpstring("Called before document is saved (may be canceled).")]`

`void BeforeDocumentSaved();`

`[id(7), helpstring("Called before right click the component.")]`

`void WindowBeforeRightClick();`

You can add your own right click menu here.

`[id(8), helpstring("Called before double click the component.")]`

`void WindowBeforeDoubleClick();`

`[id(9), helpstring("Called before double click the component.")]`

`void WindowSelectionChange();`

`[id(10), helpstring("Called before double click the component.")]`

`void DocumentBeforePrint();`

`[id(11), helpstring("Called when the file was downloaded completely.")]`

`void WindowActivate();`

[id(12), helpstring("Called when the file was downloaded completely.")]

void WindowDeactivate();

[id(13), helpstring("Called before downloading the file.")]

void BeforeDownloadFile();

[id(14), helpstring("Called when the file was downloaded completely.")]

void DownloadFileComplete();

[id(15), helpstring("Called when the file was uploaded completely.")]

void UploadComplete();

[id(16), helpstring("Called when the IE is in the protection mode.")]

void IESecurityReminder([in,out] VARIANT* Cancel);

Example

The following script to reminder the user added your site in trusted site list.

```
function edword_IESecurityReminder()
{
    edword.SetValue "Domain", "www.edrawsoft.com"
    'or you can customize the whole sentence by set the ProtectModeReminder value.
    'edword.SetValue "ProtectModeReminder", "The ActiveX Controls is not available for Internet
    sites under the protection mode. You can add www.yoursite.com to trusted site list."
}
<SCRIPT LANGUAGE=javascript FOR=edword EVENT= IESecurityReminder>
<!--
    edword_ IESecurityReminder ();
//-->
</SCRIPT>
```

Property

[id(1)] **boolean** ShowToolbars;
Shows or hides the toolbars.

[id(2)] **BSTR** LicenseName;
Sets the license name.

[id(3)] **BSTR** LicenseCode;
Sets the license code.

[id(4)] **OLE_COLOR** BorderColor;
Sets the border color the control.

[id(5)] **long** BorderStyle;
Sets the border style of the control.

Constants

```
typedef enum BorderStyle
{
    BorderNone = 0,
    BorderFlat,
    Border3D,
    Border3DThin
} BorderStyle;
```

```
typedef enum FileCommandType
{
    FileNew = 0,
    FileOpen,
    FileClose,
    FileSave,
    FileSaveAs,
    FilePrint,
    FilePageSetup,
    FileProperties,
    FilePrintPreview
} FileCommandType;
```

```
typedef enum WdSaveFormat
{
    wdFormatDocument = 0,
    wdFormatTemplate = 1,
    wdFormatText = 2,
    wdFormatTextLineBreaks = 3,
    wdFormatDOSText = 4,
    wdFormatDOSTextLineBreaks = 5,
    wdFormatRTF = 6,
    wdFormatUnicodeText = 7,
    wdFormatEncodedText = 7,
    wdFormatHTML = 8,
    wdFormatWebArchive = 9,
    wdFormatFilteredHTML = 10,
    wdFormatXML = 11
}WdSaveFormat;
```

```
typedef enum WdPrintOutRange
{
    wdPrintAllDocument = 0,
    wdPrintSelection = 1,
    wdPrintCurrentPage = 2,
    wdPrintFromTo = 3,
    wdPrintRangeOfPages = 4
}WdPrintOutRange;
```

```
typedef enum WdProtectType
{
    wdAllowOnlyRevisions = 0,
    wdAllowOnlyComments = 1,
    wdAllowOnlyFormFields = 2,
```

```
wdAllowOnlyReading = 3,  
wdNoProtection = -1,  
}WdProtectType;
```

```
typedef enum WdViewType  
{  
wdMasterView = 5,  
wdNormalView = 1 ,  
wdOutlineView = 2,  
wdPrintPreview = 4 ,  
wdPrintView = 3,  
wdReadingView = 7,  
wdWebView = 6,  
}WdViewType;
```

```
typedef enum WdRevisionType  
{  
wdRevisionAuthor = 0,  
wdRevisionDate = 1,  
wdRevisionType = 2,  
wdRevisionText = 3,  
}WdRevisionType;
```

```
typedef enum WdPasteDataType  
{  
wdPasteBitmap = 4,  
wdPasteDeviceIndependentBitmap = 5,  
wdPasteEnhancedMetafile = 9,  
wdPasteHTML = 10,  
wdPasteHyperlink = 7,  
wdPasteMetafilePicture = 3,  
wdPasteOLEObject = 0,  
wdPasteRTF = 1,  
wdPasteShape = 8,  
wdPasteText = 2,  
}WdPasteDataType;
```

```
typedef enum WdBreakType{  
wdPageBreak = 7,  
wdColumnBreak = 8,  
wdSectionBreakNextPage = 2,  
wdSectionBreakContinuous = 3,  
wdSectionBreakEvenPage = 4,  
wdSectionBreakOddPage = 5,  
wdLineBreak = 6,  
wdLineBreakClearLeft = 9,  
wdLineBreakClearRight = 10,  
wdTextWrappingBreak = 11,  
}WdBreakType;
```

```
typedef enum WdGoToItem{  
wdGoToStart = 101,  
wdGoToEnd = 102,  
wdGoToBookmark = -1 ,  
wdGoToComment = 6 ,  
wdGoToEndnote = 5 ,  
wdGoToEquation = 10 ,  
wdGoToField = 7 ,  
wdGoToFootnote = 4 ,
```

```
wdGoToGrammaticalError= 14 ,
wdGoToGraphic = 8 ,
wdGoToHeading= 11 ,
wdGoToLine = 3 ,
wdGoToObject = 9 ,
wdGoToPage = 1 ,
wdGoToPercent = 12 ,
wdGoToProofreadingError = 15 ,
wdGoToSection = 0 ,
wdGoToSpellingError = 13 ,
wdGoToTable = 2 ,
}WdGoToItem;
```

```
typedef enum WdGoToDirection{
wdGoToAbsolute = 1,
wdGoToFirst = 1,
wdGoToLast = -1 ,
wdGoToNext = 2 ,
wdGoToPrevious = 3 ,
wdGoToRelative = 2 ,
}WdGoToDirection;
```

```
typedef enum WdPageFit{
wdPageFitBestFit = 2,
wdPageFitFullPage = 1,
wdPageFitTextFit = 3 ,
wdPageFitTextNone = 0 ,
}WdPageFit;
```

```
typedef enum WdInDocPos{
wdInDocumentPosCursor = 1,
wdInDocumentPosStart = 2,
wdInDocumentPosEnd = 3 ,
}WdInDocPos;
```

```
typedef enum CommandType{
cmdTypeSave = 0x00000001,
cmdTypeClose = 0x00000002,
cmdTypePrint = 0x00000004,
cmdTypeRightClick = 0x00000008,
cmdTypeDoubleClick = 0x00000010,
cmdTypeIESecurityReminder = 0x00000020,
}CommandType;
```

```
typedef enum WdUIType
{
wdUIDisalbeOfficeButton = 0x00000001,
wdUIDisalbeNew= 0x00000002,
wdUIDisalbeOpen = 0x00000004,
wdUIDisalbeUpgradeDocument = 0x00000008,
wdUIDisalbeSave= 0x00000010,
wdUIDisalbeSaveAs= 0x00000020,
wdUIDisalbeSendAsAttachment = 0x00000040,
wdUIDisalbeClose = 0x00000100,
wdUIDisalbePrint = 0x00000200,
wdUIDisalbePrintQuick = 0x00000400,
wdUIDisalbePrintPreview = 0x00000800,
wdUIDisalbeSaveAsMenu = 0x00001000,
wdUIDisalbePrepareMenu = 0x00002000,
```

```
wdUIDisalbePermissionRestrictMenu = 0x00004000,  
wdUIDisalbeSendMenu = 0x00008000,  
wdUIDisalbePublishMenu = 0x00010000,  
wdUIDisalbeServerTasksMenu = 0x00020000,  
wdUIDisalbeCopyButton = 0x00040000,  
wdUIDisalbeCutButton = 0x00080000,  
wdUIHideMenuHome = 0x01000000,  
wdUIHideMenuInsert = 0x02000000,  
wdUIHideMenuPageLayout = 0x04000000,  
wdUIHideMenuReferences = 0x08000000,  
wdUIHideMenuMailings = 0x10000000,  
wdUIHideMenuReview = 0x20000000,  
wdUIHideMenuView = 0x40000000,  
wdUIHideMenuDeveloper = 0x80000000,  
wdUIHideMenuAddIns = 0x00100000,  
}WdUIType;
```

```
typedef enum OAEErrorCode{  
eSC_Ok = 0,  
eSC_GenericError,  
eSC_InvalidFileType,  
eSC_InvalidSite,  
eSC_WrongDNS,  
eSC_CreateTempFileFailed,  
eSC_OpenUploadFileFailed,  
eSC_SaveOpenedFileFailed,  
eSC_NotHttpURL,  
eSC_ConnectFailed,  
eSC_RequestFailed,  
eSC_RequestHeaderFailed,  
eSC_EmptyArgument,  
eSC_OpenFileArgumentFailed,  
eSC_SendRequestFailed,  
eSC_WriteDataFailed,  
eSC_ReadDataFailed,  
eSC_EndRequestFailed,  
eSC_OpenFileFailed,  
eSC_InvalidReturnData,  
}OAEErrorCode;
```

System Requirements

Hardware :

Minimum:

Pentium Based MMX processor 500 MHZ

256 MB of ram

SVGA Graphics card

64 MB HardDisk

Recommended:

Intel Celeron or AMD Duron 1 GHz and above

1 GB ram

SVGA Graphics card with some acceleration (1024x768x16bitsColor)

Software :

Minimum:

Windows 2000 with IE6 and above.

Recommended:

IE 6/7/8

Windows 2000/XP/2003/Vista/Windows 7

Office 2000/XP/2003/2007/2010

For web application: The component need IE Protection Mode was Turn Off.

You can added your site at the IE trusted site list to turn off the IE protection mode automatically when the users visit your site with the component.

Please consider also your application's requirements.

Redistribute Files

Here are the files needed for installing Edraw Viewer Component For Word.

DLL and OCX

EDWord.ocx
EDOfficeViewerX.dll

Or you can use the cab file in the install folder for web application.

edword.cab

Visual Basic Issue

How to add Office ActiveX Control to your Visual Basic 6.0 project

1. From the Project Menu select Components...
2. Select control "EDWord ActiveX Control Module" in the controls table.
3. Click the OK Button.
4. The control will now appear in your toolbox.
5. Drag and drop the control on your form.
6. Right click the control then choose the View Code... item.
7. Add the NotifyCtrlReady event and set the library file to load.

```
Private Sub EDWord1_NotifyCtrlReady()  
EDWord1.LicenseName = ""  
EDWord1.LicenseCode = ""  
End Sub
```
8. Run the project.

Visual C++ Issues

Adding the control to a simple dialog base Application

1. Begin a new MFC AppWizard(exe) dialog base Application.
2. Open The Resources Dialogs.
3. Select the Main Dialog and right click on it.
4. From pop-up menu select "Insert ActiveX Control...".
5. Select Edraw Viewer Component For Word from the list.
6. Add a member variable to newly created control in the dialog class.
7. This will automatically generate new cpp and .h files which including the information of edword control.
8. Call the MFC ClassWizard to add the control event message

To resize the control according the form add a new Window Message Handler WM_SIZE and add the following code in OnSize virtual function

```
if(!::IsWindow(m_edword.m_hWnd)) return;
```

```
m_edword.MoveWindow(0,0,cx,cy);
```

See VCEDWordDemo c++ example

Upgrade a control in VC++

You can easily upgrade a VC++ project witch is using a EDWord control of a previous version:

1. Register the new version of control using the regsvr32 utility that is located in windows system directory.
2. From Project menu select Add to Project -> Components and Controls
3. From Components and Control Gallery dialog select the folder Registered ActiveX Controls
4. Find and select Edraw Viewer Component For Word and click OK to all next dialogs.
5. Rebuild the project.

Web Application Issue

Use the edword.cab file

The component can be used for web application. You can embed it at the html Object tag.

```
<object classid="clsid: 569EB2D6-161D-4AE0-9804-640E724A297A"
id="edword" width="100%" height="100%"
codebase="http://www.yoursite.com/download/edword.cab#7,0,0,141">
</object>
```

Note: You should put the edword.cab file in your own site and change the codebase url when you distribute the component.

You can view the html samples in the install folder\samples\html folder.

The edword.cab file is available in the intall folder. You can create your own cab file.

Why do I fail to download the ActiveX control on the client machine

The failure of loading ActiveX control has the following possible causes:

1. The security settings of IE on the client machine are incorrect.

Please verify the following security settings of IE to "Prompt" or "Enabled":

- a) Download signed ActiveX controls
- b) Run ActiveX Controls and plug-ins
- c) Script ActiveX controls marked safe for scripting

The dialog box of the security setting can be launched from menu Tools>Internet Options. Then select the security tab.

How to add Edraw Component to your ASP.NET project

1. Open Visual Studio.
2. Create a new ASP.NET project.
3. Don not attempt to add the Edraw Viewer Component For Word to the Toolbox. It is a client component. You can add it as the HTML Object.

4. Copy all files at the ASP_c#\ to the new project folder.
(UploadAction.aspx UploadAction.aspx.cs Default.aspx.cs Default.aspx Tester.doc)
5. Then add exist items...
6. Modify the Server Port in the Default.aspx.
6. Run.

About the IE Protection Mode

The component can't run at the IE protection mode. So the client needs add the site in IE trusted site list. The component will pop up the reminder dialog if it run at the IE protection mode.

Convert to Full Version

The trial version has 60 day limitation.

After you put the order, you will get the full version download link and the license key.

Step:

1. Firstly you need uninstall the trial version from your computer. Make sure the edword.ocx file has been removed from your computer completed.
2. Install the full version. In the install folder, you can find all files to redistribute.
3. For VC, VB, C# destop application, you can set LicenseName and LicenseCode property directly in the Property panel.
4. For Web Application, you need set the two properies in the NotifyCtrlReady event.

```
<script language="javascript">
function edword_NotifyCtrlReady()
{
document.edword.LicenseName = "your license name";
document.edword.LicenseCode = "your license key";
}
</script>
<SCRIPT LANGUAGE=javascript FOR=edword EVENT=NotifyCtrlReady>
<!--
edword_NotifyCtrlReady();
//-->
</SCRIPT>
<object classid="clsid:6116A7EC 569EB2D6-161D-4AE0-9804-640E724A297A"
id="edword" width="100%" height="100%"
codebase="http://www.yoursite.com/download/edword.cab#7,0,0,141">
</object>
```
5. At last you can call the edword.AboutBox method to verify the license. The trial version will show "30 day trial license for evaluation". But the full license version will show your license name.

Online Store: <http://www.edrawsoft.com/edword.php>

License Agreement: <http://www.edrawsoft.com/download/edcomponentlicenseagreement.pdf>

Support Email: support@ocxt.com